Blue-White®

BW DIGI-METER®
DIGITAL PADDLEWHEEL FLOW METERS

Choose the PADDLEWHEEL FLOW METER Your Application Requires:

	F-1000	F-2000
Easy to Read LCD up to 4 Decimal Positions	✓	✓
Battery Operated	✓	RT MODEL ONLY
Flow Rate and Total Flow Display	✓	✓
Acceptable for Vertical or Horizontal Installation	✓	✓
Total Reset Function Can Be Disabled	✓	✓
Display Update Time: Rate 1.5 Sec, Total 0.5 Sec.	✓	■
Factory Calibrated	✓	✓
NIST Calibration Certificate	OPTIONAL	OPTIONAL
Custom Calibration Units Available	■	✓
NEMA 4X Weather Resistant Enclosure	✓	✓
Standard Models Ship with Pipe Fitting	✓	✓
Front Panel Security Lockout	■	✓
Panel Mounting Option Available	■	✓
4-20 mA Output (AO Option)	■	✓
Full Scale Accuracy	+/- 2%	+/- 1%
Field Programmable	■	✓
Batch Processing (PC Option)	■	✓
Output Alarm (PC Option)	■	✓
Pipe Size Range	3/8" to 12"	
Flow Range	.4 – 8,000 GPM (1 – 27,000 LPM)	

Learn more about the
PaddleWheel Flow Meters *at* www.blue-white.com

Made in USA