

# Blue-White®

## FLEXFLO® Peristaltic Metering Pumps

Choose the **FLEXFLO®** Capabilities  
Your Application Requires:



**M1**

**M2**

**M3**

**M4**

**M5**

**Flow Output Range**

.0001–5.60 GPH  
(.004–21.2 LPH)

.0085–21.23 GPH  
(.032–80.4 LPH)

.0002–33.3 GPH  
(.0007–126 LPH)

.0028–158.5 GPH  
(.0108–600 LPH)

.0076–534 GPH  
(.0286–2021 LPH)

**Turndown**

10,000:1

200:1

10,000:1

**PSI**

100 PSI (6.89 bar)

125 PSI (8.6 bar)

65 PSI (4.4 bar)

**Warranty**

5 YEAR

	BRUSHLESS	BRUSH		BRUSHLESS	
Variable Speed DC Motor TFD (Pat.#7,001,153 and 7,284,964)	✓	✓		✓	✓
Motor Reverse	■	✓		✓	✓
Tube Info Button	■	TIMER		REVOLUTION COUNTER & TIMER	
Input: Remote Start/Stop	✓	✓	✓	✓	✓
Input: 4-20mA	✓	✓	✓	✓	✓
Input: Frequency (Pulsed)	■	✓	✓	✓	✓
Output: Relay & CC	✓	✓	✓	✓	✓
Output: 4-20mA	✓	✓	✓	✓	✓
Output: Pulse	■	■	✓	✓	✓
Password Protect (PIN)	■	■	✓	✓	✓
Ethernet/IP	■	■	✓	✓	✓
Profibus	■	■	✓	✓	✓
Modbus-TCP	■	■	✓	✓	✓
NSF 61 Listed	✓	✓	✓	✓	✓

FLEXFLO® PERISTALTIC PUMPS have smooth, quiet pumping action and deliver accurate amounts of chemical to your system. Four FLEXFLO® models are offered featuring a broad range of output rates, electronics options and features. If you don't see the FLEXFLO® pump that meets your system requirements, please contact the factory. Blue-White® specializes in meeting OEM requirements.

**FLEXFLO® APPLICATIONS INCLUDE**

- |                                |                |                   |
|--------------------------------|----------------|-------------------|
| Municipal Water Treatment      | Chloramination | Caustic Injection |
| Municipal Wastewater Treatment | Fluoridation   | Alum Injection    |
| Chemical Injection             | Pac Injection  |                   |
| Chlorination                   | Acid Injection |                   |



Learn more about  
**FLEXFLO®** at [www.blue-white.com](http://www.blue-white.com)

